



## AOTLED5/CCT/M3



### Features

Architectural suspended linear for office, retail and educational applications

Die-Cast aluminum end caps

Slim profile available in White (RAL9010) and Aluminium (RAL9006)

Selectable CCT between 3000K and 4000K output

Supplied bi-directional light output as standard (directional only option can be selected if required)

Suitable for individual or continuous suspension

Supplied c/w 1.5m suspension kit as standard

Outperforms 28W and T5 fluorescent equivalent

LED lifespan L80 42,000 hours

## General Information

Lamp Type	LED
Colour / Finish	Aluminium
Emergency	Yes
Self Test	Yes
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1556
Width (mm)	61
Accessories	AOTLED/90B

## Technical Information

Wattage	45W
Lumens Delivered	4052lm (Cool White), 3861lm (Warm White)
Lm/W	92lm (Cool White), 86lm (Warm White)
CRI	Ra 80
CCT	3000/4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-25 to 50°C

Datasheet generated from <https://onetimepim.com> last updated Friday, March 26, 2021 11:29:34 AM

