

ADILED2/MWS



Features

All polycarbonate construction with opal diffuser and white trim ring.

CCT selectable between 3000K and 4000K.

14W exceeds performance of 38W CFL.

Two options of microwave sensor emergency.

/MWS/M3/CF provides CorridorFUNCTION with Tridonic control gear.

Instant light output and unlimited switching.

LED lifespan L70 56,000 hours.



Belfast: +44 (0) 2890 773750

General Information

Lamp Type	LED
Colour / Finish	White / Opal
Integral Microwave Sensor	Yes
IP Rating	IP65
Class Protection	1
Bathroom Zone	2
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	326
Depth (mm)	110
Accessories	ADI28BZ/BR, ADI28BZ/CH, ADI28BZ/SG

Technical Information

Wattage	12W
Lumens Delivered	1175lm (Cool White), 1250lm (Warm White)
Lm/W	98lm (Cool White), 104lm (Warm White)
CRI	Ra 80
ССТ	3000/4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 25°C

 $Datasheet \ generated \ from \ \underline{https://onetimepim.com} \ last \ updated \ Tuesday, \ March \ 30, \ 2021 \ 8:29:52 \ AM$



