



Local distributor code: 405638967 SEA9APN18

EAN Code: 3606489484187

Main

Range	Acti9
Product name	Acti9 Isobar P A
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Earth stud Enclosure Door Front cover Pan assembly Neutral terminal block Earth terminal block Blanking plate
Colour	Cream (RAL 9001)

Complementary

Enclosure mounting	Surface
Poles description	1P + N
[le] rated operational current	125 A at 230/240 V AC
Breaking capacity	25 kA
Overvoltage category	IV
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Incomer device options	Switch disconnector - 2P Terminal block - 2P RCCB - 2P
Protection device options at outgoer	Miniature circuit breaker (MCB) 63 A Residual current circuit breaker with overcurrent protection (RCBO) 45 A 100 mA Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A 100 mA
Number of ways	18 ways (1P) outgoer
Enclosure material	Steel
Surface treatment	Farm
	Ероху

Height	300 mm
Width	489 mm
Depth	117 mm
Net weight	5.7 kg

Environment

IP degree of protection	IP20 internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
IK degree of protection	IK05
Pollution degree	3
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-4080 °C

Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Length	50.0 cm
Number of Units in Package 1	1
Package 2 Width	100.0 cm
Package 2 Height	112.0 cm
Package 2 Weight	299.972 kg
Package 1 Width	31.0 cm
Package 1 Height	13.0 cm
Package 1 Weight	6.666 kg
Number of Units in Package 2	42
Unit Type of Package 2	P12
Package 2 Length	120.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty 18 months

Recommended replacement(s)