



## Fittings / Downlights


## Firestay 5/7W LED CCT Dimmable Wattage Switchable Fixed Downlight



Our flagship downlight has received a major facelift for 2024! The Firestay CCT now includes a 4-way colour switch and 2-way wattage switch as standard. With an upgraded 10-year warranty, the new Firestay CCT is truly a fit and forget market leading downlight.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems.
- IP65.
- Front CCT/Wattage Switch.
- Mains Dimmable as standard.
- Spacer plate options available.
- Part B / C / E compliant.
- · IC Rated.
- Fixed Screw Terminal & Lever Tool-Free Terminal options.

## **Technical Specification**



Product Code	08187V2	
Reference		

Guarantee	10 Years
EAN	5013588900001
Commodity Code	9405423990
Country of Origin	CN
UNSPSC Code	39111515







## **Technical Specification**

Volts (V)	220/240
Watts (W)	5/7
Colour Temp (K)	2700/3000/4000/6000
Dimmable?	Yes
Lumens (lm)	570-830
Candelas (cd)	550-720
Life Hours	70000
Beam Angle	60°
Energy Rating	F
CRI (ra)	85
Frequency (Hz)	50/60
IP Rating	IP65
Impact Protection	IK7
Dimensions	
Height (mm)	45
Diameter (mm)	82
Downlight Cut Out (mm)	68
Packaging Information	
Single Carton Height (mm)	100
Single Carton Width (mm)	88
Single Carton Depth (mm)	85
Single Carton Weight (kg)	0.268
Individual Volume	0.00075
Inner Box Qty	10
Inner Box Height (mm)	455
Inner Box Width (mm)	210
Inner Box Depth (mm)	95
Inner Box Weight (kg)	3.18
Outer Box Qty	20
Outer Box Height (mm)	465
Outer Box Width (mm)	220
Outer Box Depth (mm)	205
Outer Box Weight (kg)	6.42

